

NIGHTSEARCHER



TACTICAL TORCH User Manual

Before using your NightSearcher flashlight, please read this user manual, it contains important safety information and the operating instructions.

• **Technical Specification:**

Light Source: Cree XR-E Q5 LED

Light Output: 120 Lumens

Battery: 2 x CR123A batteries (included)

Running time: 3 hours

Size: L130mm x Dia. 26mm

Weight: 250g (inc. batteries)

Part No. NSTACTICAL

Durable aluminium casing / Water and shock resistant / Supplied with: tail-end switch, pressure switch, batteries and picatinny/weaver mounting bracket.

Optional Extras: Mounting bracket for telescopic sights, rechargeable version.

• **LED Assembly Replacement**

The Light Emitting Diodes (LED) can last up to 100,000 hrs and seldom need to be replaced. If there is any malfunction of the LED, please contact NightSearcher Limited or an authorised distributor.

• **Battery Replacement**

Unscrew the tailcap and insert batteries with the positive terminal towards the head, screw the tailcap to tighten it. Press the tailcap pushbutton to test.

Note: In order to protect the flashlight, please put the batteries anode (+) side toward the light's head. Reverse polarity may damage the circuit.

Warning: Batteries can explode or cause burns if disassembled, short circuited or exposed to fire or high temperature. Do not expose the contents to water, mix with used or other types of batteries.

• **ON and OFF Operation**

Tail-end switch: The switch is located in tail of the flashlight, press the switch and the flashlight will turn on continuously. The flashlight will turn off if you press the switch again.

Button & Pressure Switch: Press the pressure switch and the torch will illuminate, the pressure switch must be held for constant ON operation. The small button switch provides constant ON/OFF

• **Flashlight Maintenance**

- Use a small brush or blow dry air to clean the dust inside the reflector.
- To remove any fingerprints on the lens, use a soft cloth or cotton swab
- To prevent the O-ring from drying and threads operating smoothly, please apply petroleum jelly to these surfaces two or three times a year.
- O-ring prevents water from getting into the flashlight.
- Do not use flashlight for diving, it is not suitable for high pressure underwater environment.
- The non-anodized metal groove between the tail cap and the barrel must be cleaned periodically to ensure a good electrical contact. Always keep the tail cap spring clean.

• **NightSearcher Guarantee**

Nightsearcher products have been carefully tested and inspected before shipment and are guaranteed to be free from defective materials and workmanship for a period of 12 months from the date of purchase, provided that the enclosed instructions have been followed.

Should you experience problems with your product, please return the complete item to your purchase stockist or contact NightSearcher (details enclosed).

If upon inspection it is found that the fault occurring is due to defective materials or workmanship, repairs will be carried out free of charge. This guarantee does not apply to normal wear and tear, nor does it cover any damage caused by misuse, careless or unsafe handling, alterations, accidents, or repairs attempted by any personnel without prior approval from Nightsearcher Ltd.

Your Nightsearcher guarantee is not effective unless you can produce a dated receipt of purchase. This guarantee does not affect your statutory rights.

• **Safe disposal of waste electrical products, batteries and bulbs**



If need to dispose of this product or parts of this product: Please note that waste electrical products, batteries and bulbs should not be disposed of with household waste. Recycle where facilities exist, please check with your local authority for recycling advice.

NightSearcher Limited

Unit 4 Applied House, Fitzherbert Spur, Farlington, Portsmouth, Hampshire, PO6 1TT, UK

Tel: +44 (0)23 9238 9774 Fax: +44 (0)23 9238 9788

Web: www.nightsearcher.co.uk

Email: sales@nightsearcher.co.uk